

10 - Site Equipment



Technical Specification	
Attr <mark>ibute</mark>	Value
Numbe <mark>r of ra</mark> ys	2
Laser class	2, <1mW
Self-leveling range	4°
Tripod Connection	1/4"
Accuracy	+/-0.3 Mm / m
Indoor visibility range	10m
Laser direction	Vertical/level
Power Supply	4.5V - 3x AA

AC02234

DEWALT RED SELF LEVELLING CROSS LINE LASER

3x AA batteries can deliver over 40 hours of runtime

Built in magnetic pivot bracket mounts easily on metal surfaces

Red self-leveling cross line laser with an accuracy of ± 0.3 mm / m

Carry case protects the unit and helps maintain calibration when stored

Plated housing and thick glass protect the tool and maintain calibration

Can be used in conjunction with the DE0892 detector up to a distance of 50 metres

Self-leveling up to 4° surface angle with automatic level indication, marks a levelled line in seconds

Overmoulded housing and thick glass protects the tool and helps maintain calibration under job site conditions

Comes with: Wall mount bracket, Heavy duty carrying case, 3x AA size alkaline batteries

10-AC02234-2023-V1



www.electric-center.co.uk

Electric Center are not responsible for the accuracy and contents of this datasheet. All displayed data and specification detail has been provided by the product manufacturer.