



AC10190

Plate Switch 1G Intermediate Whi

Hard wearing, all purpose Square Edge 9mm plate with anti-microbial properties. An intermediate switch is used when you have three switches controlling one light. A typical example of this is on a landing. There is a switch at the bottom of the stairs, one at top of the stairs and one at the end of the landing. On this circuit you would need the middle switch to be intermediate (i.e. the one at the top of the stairs) in order for all the switches to function properly.

- 10AX rated
- Includes screw cap covers
- Certified to EN 60669-1

Technical Specification	
DESCRIPTION	10AX 1G Intermediate Switch
NET WEIGHT (KG)	0.057
FINISH	White
DIMENSIONS (MM)	Height - 86, Width - 86, Projection - 9
MINIMUM MOUNTING BOX DEPTH	16mm
CONSTRUCTION	Construction - Thermoset resin
IP RATING	IP20
INPUT VOLTAGE	230V 50Hz
SWITCH FUNCTION	Intermediate
EARTH TERMINAL	No
LOAD/MAX. LOAD	10AX
TERMINAL CAPACITY	2 x 1.0mm ² or 2 x 1.5mm ²
WARRANTY	15year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60669-1
ORIGIN OF MANUFACTURE	China
EAN	5051178132876

1-AC10190-2021-V1.