



AC11191

Digital 7 Day Wall Switch with Optional Dusk Start

6 different time periods (5 day plus 2 day or 7 day programming) displayed on an easy-view blue illuminated screen.

Photocell mode: The light output will only come on when the light level drops, if it is within a programmed times.

Random mode: On a random basis, it can change the ON/OFF times programmed by up to 30 minutes earlier, or later than programmed.

Manual mode: The light output is controlled by the Adv button, not the programmed times.

Automatic summer/winter time changeover.

Note: FLA01 strip light adaptor may be required in certain installations.

Technical Specification	
Operating Voltage:	230V AC 50Hz
Installation Type:	Surface
Earth Class Rating:	Class II
Operating Temperature:	0° to 40°C
Ingress Protection Rating:	IP20
Connection:	2-Wire
Power Reserve:	Up to 720 Hours
Back Box Minimum Depth:	25mm
Program Modes:	24 Hour, 7 Day, Permanent ON/OFF, Photocell (On After Dusk), Random or Timed
Switch Type:	Single or Two Way Switching (With Manual Rocker Switch Only)
Switch Rating:	Up to 200W LED with the use of the ZV900 Adapter, 40 - 400W Filament, 11 - 150W Low Energy (Min bulb size 11W), 18 - 76W Fluorescent

AC11191 - 2021 - V1