

1 - Wiring Accessories





| Technical Specification | |
|-------------------------|--------------------------------|
| Plate Dimensions | 146mm (W) x 88mm (H) x 8mm (D) |
| Maximum Voltage | 250V~ 50Hz |
| Load Rating | 13A |
| Fixing Centres | 120.6mm |
| Terminal Torque | 1.2Nm |
| Terminal Capacity | 3 x 2.5mm² or 2 x 4mm² |
| Single Pole | Yes |
| Twin Earth Terminals | Yes |
| USB Charging Output | 5V DC, 4.2A Total |
| USB Type | USB Type "A" & Type "C" |
| USB Standby Current | 2mA |
| Product Markings | DC, 5V 3A, 5V 2.4A max, 4.2A |
| Operational Temp. | -5°C to +40°C |
| Warranty | 10 Years, 1 Year Electronics |
| | |

AC12310

2G Sw. Safety Skt + USB's

- Victorian style plate
- · Satin chrome finish
- 3 pin safety shuttered socket outlets. All 3 pins of the plug must be inserted for the shutters to open
- · Supplied with white gasket
- Type A & Type C USB outlets provided
- Independent Charging: 5V DC, 4.2A USB Type A (2.4A), USB Type C (3A)
- Fits on to 25mm deep backbox
- The USB circuits within this socket outlet are designed to withstand insulation resistance tests at 500V

1-AC12310-2021-V1

