



AC3204

63A 4 Pole Enclosed Switch-Disconnecter (IP65)

IP65, 25mm cable entries, Robust polycarbonate enclosure, UV resistant, Enclosure glow wire flammability rating 960°C, Halogen free, Lower smoke generation, Padlockable in the OFF position, AC-21 Switch Rating, H:175 x W:125 x D:90mm, Enhanced safety, Easy Installation, Robust & Durable, Wide product range

| Technical Specification | |
|--------------------------------------|---|
| IEC & EN | 690V |
| UL | 600V |
| Main Switch: Isolating Voltage up to | 750V |
| Rated Impulse Withstand Voltage Uimp | 6kV |
| Rated Uninterrupted Current Iu | 40A |
| Fuse rating, class J | 70A |
| Fuse rating, class RK5 | - |
| Rated Fused short circuit current | 10A |
| Max Fuse Size (Type gL) | 63A |
| Rated Fused Short Circuit Current | 30kA |
| Single/ Multiple Strand Wire | 2.5mm ² Min 25mm ² Max |
| Fine Strand with Sleeve | 2.5mm ² Min 10mm ² Max |
| American wire gauge | 6AWG |
| Recommended Tightening Torque | 2.0Nm |

3-AC3204-2021-V1