



Technical Specificatio	n	
Cap Type	LED	
Total Power	8.8	
Lumens (Im)	660	
Beam Angle	120	
Lamp Life (Hrs)	30000	
Number of LEDs	56(28x2)	
Comparable To	60W Incandescent	
CRI	80	
ССТ (К)	3000	
Efficacy (Im/cctW)	75	
Lux at 1m	180	
Power Factor	0.5	
Height (mm)	55	
Width (mm)	100	
Length (mm)	200	

## AC444755

## 8W IP54 OVAL BULKHEAD, 3000

- $\bullet$  8W IP54 OVAL BULKHEAD, 3000K, c/w WHITE and BLACK TRIMS
- Suitable for use in sheltered outdoor common areas, gardens, hotel, pub and restaurant walkways
- LED replacement for 60W Incandescent wall/ceiling fittings
- Polycarbonate construction with high impact resistance of IK08
- UV stabilized
- Large connector block with two cable entry/exit points for ease of loop-in/loop-out
- High efficacy of 75lm/W
- Wide ambient operating temperature range of -200C to +400C
- Complete with white and black trims
- Suitable for switching by PIR, Microwave or Photocell

## 4-AC444755 -2021-V1



## www.electric-center.co.uk

Electric Center are not responsible for the accuracy and contents of this datasheet. All displayed data and specification detail has been provided by the product manufacturer.