



## AC447190

5W Fire Rated Downlight 4000K,  
60° beam angle, IP65,  
dimmable, c/w White trim

- Suitable for domestic dining, living, bathroom and bedroom spaces, hotel & office reception areas
- LED replacement for 50W halogen downlights
- LEDchroic lens replicating halogen dichroic with uniform, shadow-free light
- Low glare
- Complies with BS476 Part 21. Report and certificate from INTERNATIONAL FIRE CONSULTANTS (IFC)
- Designed and tested to retain the integrity of 30, 60 and 90 minute fire rated ceilings - compliant with Building Regulations Parts B, C and E
- Shallow profile of only 60mm depth
- Pre-wired with 0.3m of flex
- Complete with 3-way double push-in connector block allowing loop in loop out.

|                    |             |
|--------------------|-------------|
| Cap Type           | LED         |
| Total Power (W)    | 4.7         |
| Lumens (lm)        | 440         |
| Beam Angle         | 60          |
| Lamp Life (Hrs)    | 30000       |
| Number of LEDs     | 6 (6S1P)    |
| Comparable To      | 50W halogen |
| CRI                | 80          |
| CCT (K)            | 4000        |
| Efficacy (lm/cctW) | 94          |
| Lux at 1m          | 420         |
| Power Factor       | 0.9         |
| Colour             | White       |
| Cut Out (mm)       | 72          |
| Projection (mm)    | 5           |
| Recess Depth (mm)  | 55          |

4-AC447190-2021-V1