







Technical Specification		
Сар Туре	LED	
Total Power (Mkt)	6.7	
Lumens (Im)	800/850	
Beam Angle	120	
Lamp Life (Hrs)	30000	
Number of LEDs	46 (23S2P)	
Comparable To	16W T4 fluorescent	
CRI	80	
CCT (K)	3000/4000	
Efficacy (Im/cctW)	120/127	
Lux at 1m	160/170	
Power Factor	0.55	
Colour	White	
Width (mm)	22	
Length (mm)	520	

AC447200

LED linkable striplight, 520mm

- Suitable for use in cabinet displays, kitchen wall units, workbench lighting, wardrobe lighting, under counter, bed headboard
- LED replacement for 16W T4 fluorescent striplights
- Provides energy savings of up to 50% compared with traditional T4 striplights
- Switch on the side allows selection between 3000K and 4000K light output
- Complete kit includes: the fitting; 1800mm plug-in power cord; vertical and horizontal mounting clips
- 250mm, 500mm and 1000mm link cables available as accessory
- Link up to 15 fittings by plugging fittings directly together or by using linking cables
- Integral LED driver makes a fast and neat installation
- Ultra slim with integral switch. Switch all fittings on with main switch or can be individually switched
- Very high efficacy of 120-127lm/W
- Wide operating ambient temperature range of -20øC to +40øC

4-AC447200-2021-V1

