





Technical Specification	n	
Сар Туре	LED	
Total Power	13.5	
Lumens (Im)	1570/1670	
Beam Angle	120	
Lamp Life (Hrs)	30000	
Number of LEDs	74 (37S2P)	
Comparable To	30W T4 fluorescent	
CRI	80	
ССТ (К)	3000/4000	
Efficacy (Im/cctW)	117/123	
Lux at 1m	330/350	
Power Factor	0.6	
Colour	White	
Width (mm)	22	
Length (mm)	815	

## AC447202

## LED linkable striplight, 815mm

• Suitable for use in cabinet displays, kitchen wall units, workbench lighting, wardrobe lighting, under counter, bed headboard

LED replacement for 30W T4 fluorescent striplights

• Provides energy savings of up to 50% compared with traditional T4 striplights

Switch on the side allows selection between
3000K and 4000K light output

 Complete kit includes: the fitting; 1800mm plug-in power cord; vertical and horizontal mounting clips

• 250mm, 500mm and 1000mm link cables available as accessory

• Link up to 15 fittings by plugging fittings directly together or by using linking cables

• Integral LED driver makes a fast and neat installation

• Ultra slim with integral switch. Switch all fittings on with main switch or can be individually switched.

- Very high efficacy of 117-123lm/W
- Wide operating ambient temperature range of -20øC to +40øC

## 4-AC447202-2021-V1



## www.electric-center.co.uk