



AC447302

10W LED CCT selectable, IP65

- Suitable for use in retail shops, public buildings, communal areas, sports centres, stairwells, corridors, walkways
- LED replacement for 28W 2D fluorescent fittings
- Colour temperature selectable between 3000K, 4000K and 6500K
- Slim profile with a height of only 90mm
- High impact resistant polycarbonate housing providing an Impact Rating of IK09
- High efficiency Pro-diffuser allows maximum light transmission, provides low glare and creates even light distribution
- High efficacy of 84-94lm/W
- Wide operating ambient temperature range of -20°C to +40°C
- Complete with microwave sensor
- Detection range: 5m
- Adjustable time delay: 5s, 30s, 90s, 3min, 20min, 30min
- Adjustable lux settings: 2lux, 10lux, 30lux, 50lux, Disable
- Mounting height: 2.5-6m
- Suitable for 24/7 use

Technical Specification

Cap Type	LED
Total Power	9.9/9.8/10.0
Lumens (lm)	830/910/900
Beam Angle	110
Lamp Life (Hrs)	50000
Number of LEDs	60 (2x 6S5P)
Comparable To	28W 2D fluorescent
CRI	85
CCT (K)	3000/4000/6500
Efficacy (lm/cctW)	84/94/91
Lux at 1m	260/290/290
Power Factor	0.9
Colour	White
Diameter (mm)	330
Unit Weight / kg	0.93

4-AC447302-2021-V1