



AC447303

10W LED CCT selectable, IP65

- Suitable for use in retail shops, public buildings, communal areas, sports centres, stairwells, corridors, walkways
- LED replacement for 28W 2D fluorescent fittings
- Colour temperature selectable between 3000K, 4000K and 6500K
- Slim profile with a height of only 90mm
- High impact resistant polycarbonate housing providing an Impact Rating of IK09
- High efficiency Pro-diffuser allows maximum light transmission, provides low glare and creates even light distribution
- High efficacy of 69-76lm/W
- Wide operating ambient temperature range of -50°C to +35°C
- Provides 3 hour emergency discharge duration
- 130-140lm output in emergency mode
- 15% of the maintained output
- 5 year warranty for the fitting and 2 year for battery
- Suitable for switching by PIR, Microwave or Photocell
- Suitable for 24/7 use

Technical Specification

Cap Type	LED
Total Power	12.2/11.8/12.1
Lumens (lm)	830/900/900
Beam Angle	110
Lamp Life (Hrs)	50000
Number of LEDs	96 (2x 8S 6P)
Comparable To	28W 2D fluorescent
CRI	85
CCT (K)	3000/4000/6500
Efficacy (lm/cctW)	69/76/75
Lux at 1m	260/280/290
Power Factor	0.8
Colour	White
Diameter (mm)	330
Unit Weight / kg	1.09

4-AC447303-2021-V1

