



## AC447305

### 15W LED CCT selectable, IP65

- Suitable for use in retail shops, public buildings, communal areas, sports centres, stairwells, corridors, walkways
- LED replacement for 38W 2D fluorescent fittings
- Colour temperature selectable between 3000K, 4000K and 6500K
- Slim profile with a height of only 90mm
- High impact resistant polycarbonate housing providing an Impact Rating of IK09
- High efficiency Pro-diffuser allows maximum light transmission, provides low glare and creates even light distribution
- High efficacy of 82-94lm/W
- Wide operating ambient temperature range of -20°C to +40°C
- Suitable for switching by PIR, Microwave or Photocell
- Suitable for 24/7 use

| Technical Specification |                    |
|-------------------------|--------------------|
| Cap Type                | LED                |
| Total Power             | 14.7/14.3/14.7     |
| Lumens (lm)             | 1200/1340/1310     |
| Beam Angle              | 110                |
| Lamp Life (Hrs)         | 50000              |
| Number of LEDs          | 80 (2x 10S4P)      |
| Comparable To           | 38W 2D Fluorescent |
| CRI                     | 85                 |
| CCT (K)                 | 3000/4000/6500     |
| Efficacy (lm/cctW)      | 82/94/89           |
| Lux at 1m               | 380/420/410        |
| Power Factor            | 0.9                |
| Colour                  | White              |
| Diameter (mm)           | 330                |
| Unit Weight / kg        | 0.87               |

**4-AC447305-2021-V1**