



AC447307

15W LED CCT selectable, IP65

- 15W LED CCT selectable, IP65, White, 3000K, 4000K, 6500K, Emergency
- Suitable for use in retail shops, public buildings, communal areas, sports centres, stairwells, corridors, walkways
- LED replacement for 38W 2D fluorescent fittings
- Colour temperature selectable between 3000K, 4000K and 6500K
- Slim profile with a height of only 90mm
- High impact resistant polycarbonate housing providing an Impact Rating of IK09
- High efficiency Pro-diffuser allows maximum light transmission, provides low glare and creates even light distribution
- High efficacy of 69-76lm/W
- Wide operating ambient temperature range of -5°C to +35°C
- Provides 3 hour emergency discharge duration
- 140-150lm output in emergency mode
- 15% of the maintained output
- Suitable for switching by PIR, Microwave or Photocell
- Suitable for 24/7 use

Technical Specification	
Cap Type	LED
Total Power	16.8/16.7/16.7
Lumens (lm)	1150/1260/1250
Beam Angle	110
Lamp Life (Hrs)	50000
Number of LEDs	128 (2x 8S 8P)
Comparable To	38W 2D Fluorescent
CRI	85
CCT (K)	3000/4000/6500
Efficacy (lm/cctW)	69/76/75
Lux at 1m	370/400/400
Power Factor	0.9
Colour	White, Sensor
Diameter (mm)	330
Unit Weight / kg	1.09

4-AC447307-2021-V1