









Technical Specification		
Сар Туре	LED	
Total Power	14.7/14.3/14.7	
Lumens (Im)	1200/1340/1310	
Beam Angle	110	
Lamp Life (Hrs)	50000	
Number of LEDs	80 (2x 10S4P)	
Comparable To	38W 2D Fluorescent	
CRI	85	
CCT (K)	3000/4000/6500	
Efficacy (Im/cctW)	82/94/89	
Lux at 1m	380/420/410	
Power Factor	0.9	
Colour	White, Sensor	
Diameter (mm)	330	
Unit Weight / kg	0.87	

AC447308

15W LED CCT selectable, IP65

- 15W LED CCT selectable, IP65, White, 3000K, 4000K, 6500K C/W Sensor
- Suitable for use in retail shops, public buildings, communal areas, sports centres, stairwells, corridors, walkways
- LED replacement for 38W 2D fluorescent fittings
- Colour temperature selectable between 3000K, 4000K and 6500K
- Slim profile with a height of only 90mm
- High impact resistant polycarbonate housing providing an Impact Rating of IK09
- High efficiency Pro-diffuser allows maximum light transmission, provides low glare and creates even light distribution
- High efficacy of 82-94lm/W
- Wide operating ambient temperature range of -20øC to +40øC
- Suitable for switching by PIR, Microwave or Photocell
- Suitable for 24/7 use

4-AC447308-2021-V1

