



Technical Specification	
Сар Туре	LED
Total Power	174.7
Lumens (Im)	24770
Beam Angle	110
Lamp Life (Hrs)	50000
Number of LEDs	280 (4x 14S5P)
Comparable To	400W metal halide 1500W halogen
CRI	80
CCT (K)	4000
Efficacy (Im/cctW)	141
Lux at 1m	8920
Power Factor	0.97
Colour	Black
Width (mm)	487.5
Depth (mm)	59.5

## AC47095

## 170W LED flood light, IP65

• Suitable for use in decking areas, drives, pathways, sign illumination, wall washing, atriums, patios, car parks, garages, industrial units

• LED replacement for 400W Metal Halide/ 1500W Halogen flood lights

• Die cast aluminium housing providing optimal heat dissipation and high resistance to weather conditions

 Tempered glass providing high impact rating of IK07

- Complete with stainless steel screws
- Prewired with 1m of rubber flex

Pre-drilled mounting bracket with 180ø
adjustable angle

 No warm up or cool down period required by LED

- High efficacy of 141lm/W
- Wide operating ambient temperature range of -20øC to 40øC

• Suitable for switching by PIR, Microwave or Photocell

## 4-AC47095-2021-V1



## www.electric-center.co.uk