



### AC5687

## Emergency Exit Sign

The AC5687 emergency exit sign gives a streamlined installation .

The AC5687 is supplied with a full legend set and is further enhanced by our unique remote control testing option. It can be installed in both switchable maintained or non-maintained option.

#### Features

- Prismatic diffuser on underside to illuminate exit door
- Light weight & easy to install
- Optional remote control testing facility
- Maintained or Non-maintained 3 hour emergency back-up
- Incorporates 3.6V 1.5Ah NiCd battery
- Low environmental impact
- Minimal maintenance
- Meets BS EN 60598-2-22 and other relevant standards
- Optional legends available
  - . AC5688 - Arrow right
  - . AC5689 - Arrow left
  - . AC5690 - Arrow down

#### Remote Control Option

Using the AC5697 optional remote control gives the following testing options.

The AC5697 is capable of testing any number of compatible emergency lights.

Allows both monthly 5 second & annual 3-hour test.

Fittings can be tested from up to 7m

No need to fit key switches

Fitting will show a red LED if a fault is detected or Green for a pass

No need to wait for the test to complete, the indicators will remain lit until the next test or any fault is corrected.

Press once for 5 second monthly test +

### 5-AC5687-2021-V1

Technical Specification	
Light Source	4w SMT LED
IP rating	IP20
Emergency Duration	3-Hours (minimum)
Mains voltage	230v 50Hz ± 10%
Mains current	(Max) 150mA 35mA quiescent
Recharge period	Less than 24 hours
Charge indicator	Integral Green LED
Changeover voltage	As per requirements of BS EN 60598-2-22
Temperature range	5 TO 40 °C
Weight	650gm
Battery	3.6v 800mAH Nickel cadmium
Size	317W x 185H X 29mmD
Viewing distance	32m