



AC5687

Emergency Exit Sign

The AC5687 emergency exit sign gives a streamlined installation.

The AC5687 is supplied with a full legend set and is further enhanced by our unique remote control testing option. It can be installed in both switchable maintained or non-maintained option.

Features

- Prismatic diffuser on underside to illuminate exit door
- Light weight & easy to install
- Optional remote control testing facility
- Maintained or Non-maintained 3 hour emergency back-up
- Incorporates 3.6V 1.5Ah NiCd battery
- Low environmental impact
- Minimal maintenance
- Meets BS EN 60598-2-22 and other relevant standards
- Optional legends available
 - . AC5688 - Arrow right
 - . AC5689 - Arrow left
 - . AC5690 - Arrow down

Remote Control Option

Using the AC5697 optional remote control gives the following testing options.

The AC5697 is capable of testing any number of compatible emergency lights.

Allows both monthly 5 second & annual 3-hour test.

Fittings can be tested from up to 7m

No need to fit key switches

Fitting will show a red LED if a fault is detected or Green for a pass

No need to wait for the test to complete, the indicators will remain lit until the next test or any fault is corrected.

Press once for 5 second monthly test



5-AC5687-2021-V1

Technical Specification

Light Source	4w SMT LED
IP rating	IP20
Emergency Duration	3-Hours (minimum)
Mains voltage	230v 50Hz \pm 10%
Mains current	(Max) 150mA 35mA quiescent
Recharge period	Less than 24 hours
Charge indicator	Integral Green LED
Changeover voltage	As per requirements of BS EN 60598-2-22
Temperature range	5 TO 40 °C
Weight	650gm
Battery	3.6v 800mAH Nickel cadmium
Size	317W x 185H X 29mmD
Viewing distance	32m

