



### AC5714

### 5-IN-1 Emergency Exit Sign

The 5-in-1 emergency exit sign means you will always have the correct mounting method.

The 5-in-1 is supplied with a full legend set and is further enhanced by our unique remote control testing option. It can be installed in both switchable maintained or non-maintained option.

#### Features

5 Mounting options supplied as standard

- Wall
- Ceiling
- Flag
- Recessed
- Suspended
- Maintained or Non-maintained 3 hour emergency back-up
- Incorporates 3.6V 1.5Ah NiCd battery
- Low environmental impact
- Minimal maintenance
- Meets BS EN 60598-2-22 and other relevant standards

#### Remote Control Option

Using the AC5697 optional remote control gives the following testing options.

The AC5697 is capable of testing any number of compatible emergency lights.

Allows both monthly 5 second & annual 3-hour test.

Fittings can be tested from up to 7m

No need to fit key switches

Fitting will show a red LED if a fault is detected or Green for a pass

No need to wait for the test to complete, the indicators will remain lit until the next test or any fault is corrected.

Press once for 5 second monthly test

Press twice for 3 hour yearly test

LED confirms pass/fail status



### 5-AC5714-2021-V1



#### Technical Specification

Light Source	3w SMT LED
IP rating	IP50
Emergency Duration	3-Hours (minimum)
Mains voltage	230v 50Hz $\pm$ 10%
Mains current	(Max) 150mA 35mA quiescent
Recharge period	Less than 24 hours
Charge indicator	Integral Green LED
Changeover voltage	As per requirements of BS EN 60598-2-22
Temperature range	5 TO 40 °C
Weight	800gm
Battery	3.6v 800MAH Nickel cadmium
Size	344W x 237H X 42mmD (Excludes brackets)
Viewing distance	30m