



AC5725

Slim Emergency Exit Sign

The AC5725 range of 15w circular LED Luminaire offers a complete range of low profile polycarbonIP65 light fittings. It is supplied as standard with 3 colour temperature options, 3000K, 4200K & 6000K. The AC5725 range comes in a white finish as standard but is further enhanced with, black, chrome or brass coloured bezel options. Available in both mains only and emergency options a microwave sensor option with corridor function is also available. The AC5725 slim emergency bulkhead gives an excellent range of installation options.. The AC5725 may be used as both a ceiling or wall mounted light, the 15w LED array gives 1400Lm in maintained mode and 132Lm in emergency mode. **The range is further enhanced with the option of remote control testing emergency versions.**

Technical Specification

Light Source	15w SMT LED
IP rating	IP65
Emergency Duration	3-Hours (minimum)
Mains voltage	230v 50Hz ± 10%
Mains current	(Max) 450mA 200mA quiescent
Recharge period	Less than 24 hours
Charge indicator	Integral Green LED
Changeover voltage	As per requirements of BS EN 60598-2-22
Temperature range	5 TO 40 °C
Weight	108gm
Battery	3.6v 3000mAH Nickel cadmium
Size	305dia x 68mmD

Features

- 3 colour selectable: 3000K, 4200K or 6000K
- Light weight & easy to install
- IP65
- Maintained or Non-maintained 3 hour emergency back-up
- Incorporates 3.6V 3Ah NiCd battery
- Low environmental impact
- Minimal maintenance
- Meets BS EN 60598-2-22 and other relevant standards
- Incorporates push-to-test switch
- Twist on diffuser for easy installation
- Screwless terminals
- Chrome bezel - AC5728
- Black eyelid - AC5729

Remote Control Option

Using the AC5697 optional remote control gives the following testing options. The AC5697 is capable of testing any number of compatible emergency lights +

5-AC5725-2021-V1