



AC5726

Slim Emergency Exit Sign

The AC5726 range of 15w circular LED Luminaire offers a complete range of low profile polycarbonIP65 light fittings. It is supplied as standard with 3 colour temperature options, 3000K, 4200K & 6000K The AC5726 range comes in a white finish as standard but is further enhanced with, black, chrome or brass coloured bezel options. Available in both mains only and emergency options a microwave sensor option with corridor function is also available.

The AC5726 slim emergency bulkhead gives an excellent range of installation options..

The AC5726 may be used as both a ceiling or wall mounted light, the 15w LED array gives 1400Lm in maintained mode and 132Lm in emergency mode.

The range is further enhanced with the option of remote control testing emergency versions.

Technical Specification

Light Source	15w SMT LED
IP rating	IP65
Emergency Duration	3-Hours (minimum)
Mains voltage	230v 50Hz \pm 10%
Mains current	(Max) 450mA 200mA quiescent
Recharge period	Less than 24 hours
Charge indicator	Integral Green LED
Changeover voltage	As per requirements of BS EN 60598-2-22
Temperature range	5 TO 40 °C
Weight	108gm
Battery	3.6v 3000mAH Nickel cadmium
Size	305dia x 68mmD
Microwave sensor range	10M (Selectable)

Features

- 3 colour selectable: 3000K, 4200K or 6000K
- Light weight & easy to install
- IP65
- Microwave sensor with corridor function.
- Maintained or Non-maintained 3 hour emergency back-up
- Incorporates 3.6V 1.2Ah NiCd battery
- Low environmental impact
- Minimal maintenance
- Meets BS EN 60598-2-22 and other relevant standards
- Incorporates push-to-test switch
- Twist on diffuser for easy installation
- Screwless terminals
- Chrome bezel - AC5728
- Black eyelid - AC5729

Remote Control Option

Using the AC5697 optional remote control gives the following testing options.

The AC5697 is capable of testing any number of compatible

5-AC5726-2021-V1

