

6 - Ventillation, Heating & Accessories





| Technical Specification | |
|--------------------------------|-------------|
| Attribute | Value |
| Extract Performance (I/s) | 15 / 21 |
| Extract Performance (m3/hr) | 54 / 76 |
| Electrical Power Rating (W) | 5.5 / 11.8 |
| Specific Fan Power (W/I/s) | 0.37 / 0.56 |
| Sound Pressure (dBA @3M) | 22/ 34 |
| IP Rating | 4 |
| Fan Weight (Kg) | 0.65 |
| Fan Grille Height / Width (mm) | 178.5 |
| Fan Depth (mm) | 122.2 |
| Fan Spigot Diameter (mm) | 98 |
| | |
| | |
| | |
| | |

AC63012

2 speed 100mm axial fan kit

An intermittent extract pullcord fan designed to control humidity, odours and mould growth in bathrooms, shower rooms, cloakrooms and toilets.

Supplied with a remote transformer, the fan is designed specifically for safe installation directly in or over splash area zone 1.

Meets Parts F and L of Building Regulations.

Suitable for wall, ceiling and window fitting (via a Simply Silent Window Kit Plus), LV100PS comes complete with a wall-fitting kit.

Features a grille-style fascia finished in cool white

Ghost Air Movement Technology for near-silent running.

The fan has 2 speeds, selectable at install and comes complete with a 2 year Guarantee.

6-AC63012-2023-V1

