



AC63020

2 speed 100mm axial fan

An intermittent extract standard fan designed to control humidity, odours and mould growth in bathrooms, shower rooms, cloakrooms and toilets.

Meets Parts F and L of Building Regulations.

Suitable for wall, ceiling and window fitting (via a Simply Silent Window Kit Plus).

Featuring a baffle-style fascia finished in cool white, the fan comes complete with both round and square covers to maximize customer choice.

Ghost Air Movement Technology for near-silent running.

The fan has 2 speeds, selectable at install and comes complete with a 2 year Guarantee.

Technical Specification

| Attribute | Value |
|----------------------------------|------------|
| Extract Performance (l/s) | 15 / 21 |
| Extract Performance (m3/hr) | 54 / 76 |
| Electrical Power Rating (W) | 6.3 / 7.0 |
| Specific Fan Power (W/l/s) | 0.42/ 0.33 |
| Sound Pressure (dBA @3M) | 15 / 29 |
| IP Rating | 4 |
| Fan Weight (Kg) | 0.65 |
| Square Cover Height / Width (mm) | 180 / 180 |
| Round Cover Diameter (mm) | 200 |
| Fan Depth (mm) | 131 |
| Fan Spigot Diameter (mm) | 98 |
| | |
| | |
| | |

6-AC63020-2023-V1