

6 - Ventillation, Heating & Accessories





Technical Specification	
Attribute	Value
Extract Performance (I/s)	5/8/13/18
Extract Performance (m3/hr)	18 / 29 / 47 / 65
Electrical Power Rating (W)	2.0 / 2.3 / 3.1 / 3.7
Specific Fan Power (W/I/s)	0.40 / 0.29 / 0.24 / 0.21
Sound Pressure (dBA @3M)	Max. 28
IP Rating	4
Fan Weight (Kg)	0.65
Square Cover Height / Width (mm)	180 / 180
Round Cover Diameter (mm)	200
Fan Depth (mm)	131
Fan Spigot Diameter (mm)	98

AC63025

100mm dMEV axial fan

A continuous running dMEV extract fan designed to eliminate condensation, humidity and odours in bathrooms, shower rooms, cloakrooms, toilets and kitchens.

The fan boosts via an external switch and / or integral humidistat (can be set between 50 and 90% RH).

Supplied with a remote transformer, the fan is designed specifically for safe installation directly in or over splash area zone 1.

Meets Parts F and L of Building Regulations.

Suitable for wall, ceiling and window fitting (via a Simply Silent Window Kit Plus).

Featuring a baffle-style fascia finished in cool white, the fan comes complete with both round and square covers to maximize customer choice.

Ghost Air Movement Technology for near-silent running.

Fan contains an integral datalogger.

The fan comes complete with a 5 year Guarantee (motor only).

9-AC92050-2022-V1

