



6 - Ventilation & Heating



Dimensional/Line drawings to go here

Technical Specification	
Element output	490 W
Storage heater output	1062 W
Charge period	7H
Charging (7h)	7.4 kWh
Length	55 CM
Height	73 CM
Width	18 CM
Weight	59 CM
Num. of blocks (7.5kg)	-
Num. of blacks (11.5kg)	4
EAN13	8432336111167

AC6585

ECOSSH158

- o High heat retention storage heater.
- IEM technology, the intelligent way to manage the charge and the discharge.
- Weekly and daily programming.
- Three levels of temperature: Comfort, Economy and Frost-protection.
- Open window detection for reduced energy waste.
- o Adaptive start control.
- High quality insulation materials with low thermal conductivity.
- Double high heat retention materials in all sides of the storage heater.
- o Temperature sensor with calibration option.
- Overheating protection on storage heating function.
- o Balancing heating element.
- o Safety thermostat with manual reset.
- o Class I insulation.
- Storage heating elements made of stainless steel.
- $\circ\;$ Front, side and rear air isolating chambers.
- Storage core made of a specially designed material for Ecombi HHR.
- Steel structure powder coated in epoxy RAL 9010.
- o Robust thermoplastic fittings.
- o Easy to install on any kind of wall.
- Very intuitive keyboard with lock option.
 Compatible with two-period off peak electric tariff in a single 24-hour interval.

6-AC6585-2022-V1

