

6 - Ventilation & Heating





Technical Specification	
Element output	980 W
Storage heater output	2123 W
Charge period	7H
Charging (7h)	18.3 kWh
Connection	240 V-
Frequency	50-60 Hz
Length	89 CM
Height	73 CM
Width	18 CM
Weight	112 KG
Num. of blocks (7.5kg)	12
Num. of blocks (11.5kg)	
EAN13	8432336110948

AC6587

ECOSSH308

- High heat retention storage heater.
- IEM technology, the intelligent way to manage the charge and the discharge.
- $\circ\;$ Weekly and daily programming.
- Three levels of temperature: Comfort, Economy and Frost-protection.
- Open window detection for reduced energy waste.
- Adaptive start control.
- High quality insulation materials with low thermal conductivity.
- Double high heat retention materials in all sides of the storage heater.
- $\circ\;$ Temperature sensor with calibration option.
- Overheating protection on storage heating function.
- Balancing heating element.
- \circ Safety thermostat with manual reset.
- o Class I insulation.
- Storage heating elements made of stainless steel.
- $\circ\;$ Front, side and rear air isolating chambers.
- Storage core made of a specially designed material for Ecombi HHR.
- Steel structure powder coated in epoxy RAL 9010.
- Robust thermoplastic fittings.
- Easy to install on any kind of wall.
- Very intuitive keyboard with lock option.
 Compatible with two-period off peak electric tariff in a single 24-hour interval.

6-AC6587-2022-V1



www.electric-center.co.uk

Electric Center are not responsible for the accuracy and contents of this datasheet. All displayed data and specification detail has been provided by the product manufacturer.