



AC6591

MAC15



Dimensional/Line drawings to go here

- o Heating boiler made of insulated steel.
- o Modulating electronic control of the heater by SEM system (Smart Electronic Modulating system).
- o 50L DHW tank made of insulated stainless steel, CFC free.
- o Stainless steel shielded elements - INCOLOY800 for heating and DHW.
- o 6L heating expansion vessel.
- o 3L DHW expansion vessel.
- o Modulating electronic control of the heater.
- o Pressure gauge 0-4bar.
- o Circulating pump.
- o Auto air vent.
- o Silent TRIAC power switches.
- o Auto Heating Regulation mode.
- o Heating flow detector.
- o Heating temperature limiter 100°C.
- o DHW temperature limiter 80°C.
- o Heating 3 bar relief valve.
- o DHW 7 bar relief valve.
- o Also suitable for use with under floor heating.
- o DHW anti-electrolysis hoses.
- o Powder coated RAL 9010.
- o Wall bracket steel template to set up connections easily.
- o Compatible with the Elnur "RSTAT" Ambient Thermostat and the Elnur Connected range of internet thermostats, all available as accessories.

Technical Specification

Selectable Output (KW)	3-15 kW
Kcal/h	2580-12900 kcal/h
Current 3 X400 V+N-A	13-21.7
Current 230 V-A	113-52.2
Time Available DHW	29'04"-5'49"
Volatage (V)	3x400 V+N/220-240
Frequency (Hz)	50-60
Insulation	Class 1
Height	83 CM
Width	55.5 CM
Depth	45 CM
Weight	61 CM
EAN13	8432336804663

6-AC6591-2022-V1