



AC66333

9.3m² Underfloor Heating Mat

A high powered underfloor heating mat suitable for use with tile, stone and brick or flagstone flooring.

The 240W/sqm range is the fastest reacting, high-output system on the U.K. market and the ultra-thin cable on mesh construction ensures floor levels are only raised by a few millimetres.

The high output is ideal for sole source heating in very small areas such as en-suites or in much larger high heat loss areas such as foyers and conservatories.

Mix and match with other 240W/sqm mat sizes to provide the perfect coverage whatever the size of your room.

Technical Specification	
Mat Size	9.3m ² - 18.6m x 0.5m
Output	240W/sqm - 2210W
Loading	9.6 Amps
Resistance	26 Ohms
Maximum Cable Load	20W/metre
Coldtail Lead	4m double insulated fully earthed cable
Wire Thickness	2.7 - 3.2mm
Cable Flexibility	Minimum bend radius 18mm
Inner Insulation	Fluoropolymer (FEPY7) 200°C
Outer Insulation	Mechanical protection from PVC(Y) 90°C
Earth Protection	100% aluminium earth shield
Manufactured In	Denmark
Approvals	BEAB Approved Cable, UKCA, CE, IPX7
Approved To	EN 60335-1:1998, EN60335-2-17:1999, IEC 60730
Compliant With	Part L, 18 th Edition IEE Wiring Regulations

- Suitable for sole source heating in even the smallest rooms
- Cut-and-turn system for easy installation
- Zero-float mesh for use with levelling compounds
- Particularly well suited to very small rooms where heat loss is higher
- Suitable for use beneath thick floor coverings such as brick or stone
- Perfect for drying out floors around swimming pools or in wetrooms
- Quick and easy to install
- 3mm cable for ultra-low build height
- 4m coldtail so no extension required on site
- Lifetime Warranty

6-AC66333-2021-V1