



AC6947

Undersink 5 Litre Vented Point of Use Water Heater

- 5 litre capacity
- Supplies hot water to a single sink
- Easy to install
- Stylish design and slimline profile
- Undersink mounting
- Comes complete with vented mixer tap and hoses
- ErP Energy Efficiency Class A
- Safety thermal cut-out can be re-set rather than requiring to be replaced
- 2 kW element
- External temperature control with frost protection setting
- Neon element on indicator
- Cable pre-wired (1m)
- No need for expansion vessel, relief valve or reducing valve
- Must be used with supplied vented mixer tap

Technical Specification	
Capacity	5 litres
Power	2 kW
Outer Casing	Easy clean high impact plastic
Controls	Thermostat adjustable to approx. 80°C
Safety	Safety resettable thermal cut-out
	Frost protection setting when power is on
	Open outlet non-pressurised system, vented mixer tap must be used
ErP Energy Efficiency	Class A
Standing Loss	0.32 kWh/ day
IP Rating	IP24
Water Pressure	Minimum water pressure 0.5 bar, maximum water pressure 8 bar
Electrical Connection	Cable pre-wired (1m)
Dimensions	h x w x d (mm) 400 x 270 x 180
Approvals	CE, UKCA
Warranty	1 year parts or replacement warranty

6-AC6947-2022-V1