

## 6 - Ventilation & Heating





Technical Specification	
Capacity	3 litres
Power Rating	2.84 kW
Outer Casing	Easy clean high impact polycarbonate/abs
Tank	Stainless Steel
Controls	Robust heavy duty control valve
Standing Loss	0.55 kWh/day, 23 W
IP Rating	IPX0
Water Pressure	Minimum water pressure 1 bar, maximum water pressure 10 bar
Electrical Connection	Cable pre-wired (1.5m) to the bottom left
Dimensions	h x w x d (mm) 500 x 330 x 255
Approvals	CE, UKCA, WRAS
Maintenance	Descale every 6 months
Warranty	1 year on site warranty

## AC6949

## **Boiling Water Heater Wall Mounting 5L White**

- Instant boiling water
- 5 litre capacity
- Sleek ergonomic design
- 2.84 kW gives fast heat up time
- Time saving no need to wait for the kettle to boil
- Space saving frees up worktop space by eliminating the need for a kettle
- Energy efficient standing losses only 23 W
- Status ring on base of control valve to indicate ready or heating (green/ red LED)
- Autocalibration for optimal temperature
- Cool touch control valve and water outlet reduce heat losses
- Simple to use and easy to install
- Designed and assembled in the UK
- One year on site warranty
- Initial draw off 30 cups, recovery rate 166 cups per hour (based on 167 ml cup)
- It is highly recommended that a filter system is fitted to protect against scale build up

6-AC6949-2022-V1.

