



Section 9 - Renewables



Technical Specification	
Input Amps	32a Single Phase
Input voltage	230V AC
Input frequency	50/60HZ
Output voltage	230V AC
Max. output power	7.3KW
Max. output current	32A
Charging interface type	IEC 62196-2, Type 2
Protection degree	IP65
Environment temp	-25°C~+50°C
Relative humidity	0-95% non-condensing
Cooling	Natural air cooling
Standby consumption	8W
IK Rating	IK10
Dimension (W/H/D)	240/380/145mm
Weight	5KG

AC92003C

7.3kW Pro Earth Wall Charger

The AC92003C is a single-phase, fast AC electric vehicle charger, that comes with built-in Pro Earth protection, meaning the charger does not require the addition of a costly earth spike installation.

Our 7.3kW pro earth charging unit comes packed with features as well as a market-leading five-year warranty. Complete with a compact sleek design and solar compatibility; this charger also has time-shifting capabilities giving you the opportunity to save £100's per year*. With the charging unit's integrated cable locking feature you can ensure total protection, granting safety and convenience tethering the charger, cable, and vehicle all together securely

With a CT clamp included as standard, to enable dynamic load management and solar capabilities via the charger settings, the AC92003C is ready out of the box and perfect for any domestic electric vehicle charging. The RFID unit comes with one RFID card as standard, with additional RFID cards available for purchase. Optional ground mounts (AC92021) & optional floor stands (AC92020) are available to purchase.













9-AC92003C-2023-v1

