



AC447193

7W IP65 Fire Rated Downlight

- Suitable for domestic dining, living, bathroom and bedroom spaces, hotel & office reception areas
- LED replacement for 50W LV halogen downlights
- Colour temperature selectable; switch on the back of the fitting allows selection between 3000/4000/6000K
- LEDchroic lens replicating halogen dichroic with uniform, shadow-free light
- Tested for use with I-Joists & Metal Web Joists
- Complies with BS476 Part 21. Report and certificate from INTERNATIONAL FIRE CONSULTANTS (IFC)
- Designed and tested to retain the integrity of 30, 60 and 90 minute fire rated ceilings - compliant with Building Regulations Parts B, C and E
- Shallow profile of only 60mm depth
- Prewired with 0.3m of flex
- Complete with 3-way double push-in connector block allowing loop in loop out
- Chrome and brushed chrome trims available as an accessory
- High efficacy of 77-94lm/W

Technical Specification

Cap Type	LED
Total Power	6.8/6.6/6.8
Lumens (lm)	520/610/550
Beam Angle	60
Lamp Life (Hrs)	30000
Number of LEDs	1
Comparable To	50W LV halogen
CRI	80
CCT (K)	3000/4000/6000
Efficacy (lm/cctW)	77/94/83
Lux at 1m	670/700/570
Power Factor	0.9
Colour	White
Cut Out (mm)	72
Projection (mm)	5

4-AC447193 -2021-V1

